Design & specification considerations

Brickwork Bonds and net quantities per m²

	Half brick thick	•	One brick thick (215mm)						
	bricks cut on si			Takal	Chuatabaua	Handous			
Chuchala au Daurd	Total	Stretchers	Headers	Total	Stretchers	Headers			
Stretcher Bond	All stretchers 65mm								
	73mm	60	0	120	120	0			
	54	54	0	108	108	0			
Header Bond	All headers (assuming each brick for a 102mm wall cut on site and best half								
	used.)								
	119	0	119	119	0	119			
English Bond	Alternate courses of headers and stretchers.								
	90	30	60	120	60	60			
English Garden	Stretchers with rows of headers every 4 th or 6 th course.								
Wall	73	46	27	128	92	27			
Every 4 th course									
(commencing with 3 stretcher rows) Every 6 th course	68	50	18	118	100	18			
(commencing with									
5 stretcher rows)									
Flemish Bond	Alternate bricks, header/stretcher, in each course.								
	80	40	40	120	80	40			
Flemish Garden	3 Stretchers to c				T				
Wall	68	51	17	119	102	17			
Stack Bond	All stretchers with perpends directly above the perpend below.								
	60	60	0	Not recommended both sides.					





TECHNICAL INFORMATION SHEET

A4Page 2

Design & specification considerations

		2mm) accumin	One brick thick (215mm)						
	Half brick thick (102mm) assuming half bricks cut on site and best half selected.			One blick thick (213mm)					
	Total	Stretchers	Headers	Total	Stretchers	Headers			
Manle Dand									
Monk Bond	2 stretchers to 1 header. Header laid centrally over the perpend between the 2								
	stretchers below.								
	72	48	24	120	96	24			
	0: 11 . 5 1: 1			<u> </u>					
English Cross	Similar to English Bond but a header is placed next to the end stretcher on								
Bond	every alternate stretcher course.								
	89	30	59	119	60	59			
Rat Trap	Brick on edge 1 stretcher/ 1 header (but can be 3 to 1 variants).								
	Na – 215mm only			90	60	30			
cavity_									
Quetta Bond	Reinforcing bond usually filled with steel rods and mortar. Alternate bricks laid								
Current Borrier seriors con	header/stretcher with the back end of the header lining up with the centre of								
	the stretcher on the rear.								
	Na - 1 ½ brick thick only (327mm)			164	82	82			
	172 Shok thick only (32711111)			104	02	02			
Decreed Deced	Alternate rows of stretchers on edge and headers on flat.								
Dearne's Bond		stretchers on							
	Na – 215mm only			96	48	48			
Diamond	Alternate rows of all headers / 1 stretcher to 2 headers. Off-set stretchers every								
Diaper	6 th course.								
	104	15	89	119	30	89			
			(53						
			coloured)						

For further information or advice regarding this topic please contact Ibstock's Design & Technical Helpline on **0844 800 4576** or email <u>technical@ibstock.co.uk</u>

Although the instructions contained in this publication and any other information published by Ibstock Brick Ltd are believed to be accurate at the date of publication, they are strictly for guidance only and Ibstock Brick Ltd accepts no liability in relation to their use or for any losses, howsoever caused. You are responsible for taking all reasonable steps to ensure your use of the product conforms to all applicable health and safety requirements from time to time. If in doubt, please consult appropriately qualified persons. All products sold by Ibstock are sold subject to Ibstock's Terms and Conditions of Sale, a copy of which is available on request.



